

View Online at <https://aerobasegroup.com/nsn/5305-01-575-8490>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.262 inches and 1.302 inches

**Fastener Length:**

Between 1.460 inches and 1.500 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.600 inches and 0.656 inches

**Head Height:**

0.198 inches

**Internal Drive Style:**

Hexagon

**End Application:**

2320-01-549-8611 truck, cargo

**Thread Diameter:**

0.313 inches

**Width Across Flats:**

0.188 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

7800 pounds per square inch

**Countersink Angle:**

Between 80.0 degrees and 84.0 degrees

**Product Name:**

Screw. Cap, socket head, flat countersunk

**Material:**

Steel

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Zinc

**Surface Treatment Specification:**

Astm b633, type ii. Class fe/zn 5 assn standard single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0