Hexagon Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-576-2852

Thread Length: 2.250 inches Fastener Length: 2.250 inches Head Style: Hexagon Head Height: 0.312 inches Width Between Flats: 0.750 inches End Application: 5895-01-495-9106, light Thread Diameter: 0.500 inches Thready Qty Per Inch (13 Min. Tensile Strength (70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	osi):	ninal v2		
Right-hand Thread Length: 2.250 inches Fastener Length: 2.250 inches Head Style: Hexagon Head Height: 0.312 inches Width Between Flats: 0.750 inches End Application: 5895-01-495-9106, light Thread Diameter: 0.500 inches Thready Qty Per Inch (13 Min. Tensile Strength (70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	pi): osi):	ninal v2		
Thread Diameter: 0.500 inches Thready Qty Per Inch (* 13 Min. Tensile Strength (* 70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name:	pi): osi):	ninal v2		
2.250 inches Fastener Length: 2.250 inches Head Style: Hexagon Head Height: 0.312 inches Width Between Flats: 0.750 inches End Application: 5895-01-495-9106, light Thread Diameter: 0.500 inches Thready Qty Per Inch (13 Min. Tensile Strength (70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	pi): osi):	ninal v2		
Fastener Length: 2.250 inches Head Style: Hexagon Head Height: 0.312 inches Width Between Flats: 0.750 inches End Application: 5895-01-495-9106, light Thread Diameter: 0.500 inches Thready Qty Per Inch (13 Min. Tensile Strength (70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	pi): osi):	ninal v2		
2.250 inches Head Style: Hexagon Head Height: 0.312 inches Width Between Flats: 0.750 inches End Application: 5895-01-495-9106, light Thread Diameter: 0.500 inches Thready Qty Per Inch (13 Min. Tensile Strength (70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	pi): osi):	ninal v2		
Head Style: Hexagon Head Height: 0.312 inches Width Between Flats: 0.750 inches End Application: 5895-01-495-9106, light Thread Diameter: 0.500 inches Thready Qty Per Inch (13 Min. Tensile Strength (70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	pi): osi):	ninal v2		
Hexagon Head Height: 0.312 inches Width Between Flats: 0.750 inches End Application: 5895-01-495-9106, light Thread Diameter: 0.500 inches Thready Qty Per Inch (13 Min. Tensile Strength (70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	pi): osi):	ninal v2		
Head Height: 0.312 inches Width Between Flats: 0.750 inches End Application: 5895-01-495-9106, light Thread Diameter: 0.500 inches Thready Qty Per Inch (13 Min. Tensile Strength (70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	pi): osi):	ninal v2		
0.312 inches Width Between Flats: 0.750 inches End Application: 5895-01-495-9106, light Thread Diameter: 0.500 inches Thready Qty Per Inch (13 Min. Tensile Strength (70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	pi): osi):	ninal v2		
Width Between Flats: 0.750 inches End Application: 5895-01-495-9106, light Thread Diameter: 0.500 inches Thready Qty Per Inch (13 Min. Tensile Strength (70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	pi): osi):	ninal v2		
0.750 inches End Application: 5895-01-495-9106, light Thread Diameter: 0.500 inches Thready Qty Per Inch (13 Min. Tensile Strength (70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	pi): osi):	ninal v2		
End Application: 5895-01-495-9106, light Thread Diameter: 0.500 inches Thready Qty Per Inch (* 13 Min. Tensile Strength (* 70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	pi): osi):	ninal v2		
5895-01-495-9106, light Thread Diameter: 0.500 inches Thready Qty Per Inch (13 Min. Tensile Strength (70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	pi): osi):	ninal v2		
Thread Diameter: 0.500 inches Thready Qty Per Inch (* 13 Min. Tensile Strength (* 70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	pi): osi):	ninal v2		
0.500 inches Thready Qty Per Inch (13 Min. Tensile Strength (70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	osi):			
Thready Qty Per Inch (13 Min. Tensile Strength (70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	osi):			
13 Min. Tensile Strength (70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	osi):			
Min. Tensile Strength (70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel				
70000 pounds per squar Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel				
Hardness Rating: 70.0 rockwell b Product Name: Type 316 stainless steel	e inch			
70.0 rockwell b Product Name: Type 316 stainless steel				
Product Name: Type 316 stainless steel				
Type 316 stainless steel				
Special Features:	hex head cap screw			
finish is plain				
Material:				
Steel comp 316				
Thread Series Designa	tor:			
Unc				
Specification Data:				
80204-01-01-1996 - revi	sion 2005 professional/indust	ial association	standard	
Shelf Life:				
N/a				
Unit Of Measure:				
Demilitarization:				
No				
Fiig:				