NSN 5305-01-576-3554

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-576-3554

View Online at https://aerobasegroup.com/nsn/5305-01-576-3554
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.338 inches
Fastener Length:
1.026 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.339 inches and 0.381 inches
Grip Diameter:
0.189 inches
Internal Drive Style:
Offset cruciform (torque set)
End Application:
Nimrod mra4; nimrod 2000; air reconaissance
Thread Diameter:
0.190 inches
Grip Length:
0.688 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Bolt, 100 degree flush head, 160, 000 psi uts
Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740
Material Specification:
Mil-s-5626, uns g41400 military specification 1st material response or ams6415, uns g43400 assn standard 2nd material response or
$mil\text{-s-}5000,\ e4340\ (unsg43406)\ military\ specification\ 3rd\ material\ response\ or\ mil\text{-s-}6049,\ unsg87400\ military\ specification\ 4th\ material\ materia$
response
Surface Treatment:
Cadmium
Thread Series Designator:
Unjf
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5305-01-576-3554

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.