NSN 5305-01-576-3598

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-576-3598

View Online at https://aerobasegroup.com/nsn/5305-01-576-3598	
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.425 inches	
Fastener Length:	
1.925 inches	
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.464 inches and 0.506 inches	
Grip Diameter:	
0.189 inches	
Internal Drive Style:	
Offset cruciform (torque set)	
End Application:	
Nimrod mra4; nimrod 2000; air reconnaissance	
Thread Diameter:	
0.250 inches	
Grip Length:	
1.500 inches	
hready Qty Per Inch (tpi):	
28	
Min. Tensile Strength (psi):	
160000 pounds per square inch	
Countersink Angle:	
09.0 degrees and 101.0 degrees	
Product Name:	
Bolt, 100 degree flush head 160, 000 psi uts	
Material:	
Steel comp 4140 or steel comp 4340 or steel comp 8740	
Material Specification:	
Mil-s-5626, uns g41400 military specification single material response or ams6415, e4340 (g43400) assn sta	andard single material
response or mil-s-5000, uns g43406 military specification single material response or mil-s-6049, uns g8740	00 military specification single
material response	
Surface Treatment:	
Cadmium	
Thread Series Designator:	
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 5305-01-576-3598

Close Tolerance Screw - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.