NSN 5305-01-576-3692

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-576-3692 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.338 inches **Fastener Length:** 1.526 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.339 inches and 0.381 inches **Grip Diameter:** 0.189 inches **Internal Drive Style:** Offset cruciform (torque set) **End Application:** Nimrod mra4; nimrod 2000; air reconnaissance **Thread Diameter:** 0.190 inches **Grip Length:** 1.188 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, 100 degree flush head, 160, 000 psi uts **Special Features:** Threads have drilled hole, 0.070 - 0.080 inch in dia. Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5626, uns g41400 military specification single material response or ams6415, e4340 (uns g43406) assn standard single material response or mil-s-5000, unsg43406 military specification single material response or mil-s-6049, uns g87400 military specification single material response **Surface Treatment:** Cadmium

N/a

Unjf

Shelf Life:

Thread Series Designator:

NSN 5305-01-576-3692

Close Tolerance Screw - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.