NSN 5305-01-578-1144

Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-578-1144

| Thread Direction: |
|--|
| Right-hand |
| Thread Length: |
| 22.0 millimeters |
| Fastener Length: |
| Between 69.4 millimeters and 70.6 millimeters |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 15.6 millimeters and 16.0 millimeters |
| Internal Drive Style: |
| Hexagon |
| End Application: |
| Mrap; cougar e1u |
| Thread Diameter: |
| 8.0 millimeters |
| Width Across Flats: |
| Between 5.0 millimeters and 5.1 millimeters |
| Thread Pitch In Millimeters: |
| 1.25 |
| External Thread Tolerance Class: |
| 6g |
| Special Features: |
| Surface treatment is black oxide |
| Color: |
| Black |
| Material: |
| Steel property class 10.9 |
| Material Specification: |
| Iso 898 assn standard single material response |
| Surface Treatment: |
| Oxide |
| Thread Series Designator: |
| Μ |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |
| |