

View Online at <https://aerobasegroup.com/nsn/5305-01-579-5360>

**Thread Direction:**

Right-hand

**Thread Length:**

26.0 millimeters

**Fastener Length:**

Between 9.0 millimeters and 10.0 millimeters

**Head Style:**

Hexagon

**Head Height:**

Between 3.2 millimeters and 3.5 millimeters

**Width Between Flats:**

Between 9.7 millimeters and 10.0 millimeters

**Internal Drive Style:**

Torque set

**End Application:**

Nsn 2320-01-565-3428 chassis, truck

**Thread Diameter:**

6.0 millimeters

**Min. Tensile Strength (psi):**

1100 megapascals

**Thread Pitch In Millimeters:**

1.0

**Product Name:**

Screw, dual, wrenching, hex head/offset cruciform, a286 cres, full thread, 1100 mpa-metric

**Screw Material:**

Stainless steel

**Screw Material Specification:**

A286 assn standard single material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Bearing Surface Of Head Surface Finish:**

0.8 micrometers

**Shank Surface Finish:**

0.8 micrometers

**Thread Surface Finish:**

0.8 micrometers

**Thread Series Designator:**

Mj

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A500d0