

View Online at <https://aerobasegroup.com/nsn/5305-01-579-7071>

**Thread Direction:**

Right-hand

**Thread Length:**

12.0 millimeters

**Fastener Length:**

18.0 millimeters

**Head Style:**

Fillister

**Head Diameter:**

10.0 millimeters

**Head Height:**

6.0 millimeters

**Internal Drive Style:**

Hexagon

**End Application:**

Guide winch assembly

**Thread Diameter:**

6.0 millimeters

**Width Across Flats:**

0.130 inches

**Min. Tensile Strength (psi):**

19800 newtons per square millimeter

**External Thread Tolerance Class:**

2a

**Product Name:**

Inavy: sch cap screw; std: screws, cap, hexagon socket head, full thread, a-286, 1100mpa, metric

**Special Features:**

1100 mpa; head is drilled 0.4mm, 1.4 mm from top; point is flat and chamfered 45 degrees from dia. Of 4.7 mm

**Material:**

Stainless steel

**Material Specification:**

A-286 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams2700 assn standard single treatment response

**Thread Series Designator:**

Mj

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0