NSN 5305-01-580-6309

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-580-6309



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.578 inches and 0.595 inches Fastener Length: Between 2.157 inches and 2.204 inches **Head Style:** Pan **Head Diameter:** Between 0.594 inches and 0.615 inches **Head Height:** Between 0.203 inches and 0.218 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.313 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Product Name:** Screw, machine - pan head, structural, cross recessed **Screw Material:** Steel comp 8630 or steel comp 8740 or steel comp 4130 **Screw Material Specification:** Mil-s-7839 military specification single material response or mil-s-6049 military specification single material response **Head Surface Treatment:** Cadmium **Screw Surface Treatment:** Cadmium **Head Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Screw Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unf

Shelf Life:

N/a

NSN 5305-01-580-6309

Machine Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-7839 spec.

