NSN 5305-01-580-6449

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-580-6449 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.781 inches **Fastener Length:** 1.406 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.688 inches and 0.755 inches **Shoulder Diameter:** 0.499 inches all shoulders **Shoulder Length:** 0.516 inches all shoulders **Internal Drive Style:** High-torque **End Application:** F-15 aircraft **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round all shoulders Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Mil-c-83488, type ii, class 3 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-580-6449

Shoulder Screw - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.