## NSN 5305-01-580-9158

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-580-9158

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.260 inches  |
|   |
| Fastener Length:<br>Between 0.511 inches and 0.541 inches |
|   |
| Head Style:<br>Pan  |
| Fan<br>Head Diameter:                                     |
|   |
| Between 0.306 inches and 0.322 inches                     |
| Head Height:  |
| Between 0.105 inches and 0.115 inches                     |
| Grip Diameter:  |
| 0.289 inches  |
| Point Diameter:   |
| Between 0.162 inches and 0.163 inches                     |
| Point Style:  |
| Flat  |
| Internal Drive Style:                                     |
| Offset cruciform (torque set)                             |
| Thread Diameter:  |
| 0.164 inches  |
| Grip Length:  |
| Between 0.240 inches and 0.260 inches                     |
| Thready Qty Per Inch (tpi):                               |
| 32  |
| Material:   |
| Titanium alloy uns r56400                                 |
| Material Specification:                                   |
| Ams4967 assn standard single material response            |
| Surface Treatment:  |
| Aluminum  |
| Surface Treatment Specification:                          |
| Nas4006 assn standard single treatment response           |
| Thread Series Designator:                                 |
| Unjc  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

## NSN 5305-01-580-9158

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

