NSN 5305-01-580-9990

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-580-9990

| Thread Class: |
|--|
| |
| 3a Thread Direction: |
| Thread Direction: |
| Right-hand |
| Thread Length: Between 0.318 inches and 0.328 inches |
| |
| Fastener Length: Between 0.933 inches and 0.963 inches |
| |
| Head Style: Flat countersunk |
| Head Diameter: |
| 0.322 inches |
| Grip Diameter: |
| Between 0.1881 inches and 0.1895 inches |
| |
| Internal Drive Style: |
| Cross recess type 1 Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.620 inches and 0.630 inches |
| |
| Thready Qty Per Inch (tpi): 32 |
| SZ Countersink Angle: |
| 100.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Product Name: |
| Bolt, pan head, cross recess, short thread |
| Material: |
| Titanium alloy |
| Material Specification: |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Surface Treatment: |
| Aluminum |
| Surface Treatment Specification: |
| Bms 10-85, type 1 assn standard single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |

NSN 5305-01-580-9990

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

