## NSN 5305-01-582-4805



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-582-4805 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** Between 0.501 inches and 0.520 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.226 inches and 0.257 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches **Grip Length:** 0.188 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig: A003b0

No

## NSN 5305-01-582-4805

Close Tolerance Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.