NSN 5305-01-583-3077

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-583-3077 **Thread Class:** 2a **Thread Direction:** Right-hand **Fastener Length:** 1.000 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.256 inches and 0.294 inches **Head Height:** Between 0.087 inches and 0.097 inches **Washer Quantity: Internal Drive Style:** Cross recess type 1 **End Application:** 77c732600g001 (03538) an/blq10 (v) 4 fy04 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** 0.250 inches **Secondary Washer Outside Diameter:** Between 0.302 inches and 0.322 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.031 inches **Secondary Washer Material Thickness:** Between 0.025 inches and 0.035 inches **Product Name:** Screw machine Material: Steel comp 302 and steel comp 303 and steel comp 304 **Surface Treatment:**

Passivate

NSN 5305-01-583-3077

Assembled Washer Screw - Page 2 of 2



Fiig: A003b0