NSN 5305-01-583-3140

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-583-3140 **Thread Class:** 2a **Thread Direction:** Right-hand **Fastener Length:** 0.375 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.238 inches **Head Height:** Between 0.070 inches and 0.080 inches **Washer Quantity: Internal Drive Style:** Cross recess type 1 **End Application:** An/blq-10 (v) 1 fy06 prod w/pepi 3 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** 0.209 inches **Secondary Washer Outside Diameter:** 0.260 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.025 inches **Secondary Washer Material Thickness:** 0.040 inches **Product Name:** Screw assembly panel Material: Steel comp 302 and steel comp 303 and steel comp 304

Surface Treatment:

Passivate

NSN 5305-01-583-3140

Assembled Washer Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0