NSN 5305-01-585-4567

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-585-4567

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.763 inches and 0.773 inches **Fastener Length:** Between 1.565 inches and 1.595 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.6901 inches and 0.7611 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.500 inches **Grip Length:** Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, shear, 100 degree flush reduced head, offset cruciform, 95 ksi fsu Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1581 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-01-585-4567

Close Tolerance Screw - Page 2 of 2



	• •						
ın	1+	Of	ΝЛ	ດລ	CI.	ırı	ο.

--

Demilitarization:

No

Fiig:

A003b0