## NSN 5305-01-585-8067

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-585-8067

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| с<br>С   |
| Thread Length:<br>Between 0.251 inches and 0.301 inches    |
|  |
| Fastener Length:<br>Between 0.661 inches and 0.705 inches  |
|  |
| Head Style:  |
| Modified pan Head Diameter:                                |
|  |
| Between 0.309 inches and 0.331 inches                      |
| Head Height:   |
| Between 0.088 inches and 0.102 inches                      |
| Grip Diameter:   |
| Between 0.1625 inches and 0.1635 inches                    |
| Internal Drive Style:                                      |
| Offset cruciform (torque set)                              |
| Thread Diameter:   |
| 0.164 inches   |
| Grip Length:   |
| Between 0.302 inches and 0.322 inches                      |
| Thready Qty Per Inch (tpi):                                |
| 32   |
| Min. Tensile Strength (psi):                               |
| 160000 pounds per square inch                              |
| Surface Finish:  |
| 32.0 microinches threads                                   |
| Material:  |
| Stainless steel  |
| Material Specification:                                    |
| Ams 5737 assn standard single material response            |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:                           |
| Qq-p-35 federal specification single treatment response    |
| Thread Series Designator:                                  |
|  |
| Specification Data:  |
| 80205-nas1142 professional/industrial association standard |
| Shelf Life:  |
| N/a  |

## NSN 5305-01-585-8067

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

