NSN 5305-01-586-1954

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-586-1954 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 0.974 inches and 1.018 inches **Head Style:** Modified pan **Head Diameter:** Between 0.309 inches and 0.331 inches **Head Height:** Between 0.088 inches and 0.102 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.164 inches **Grip Length:** Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1124 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-586-1954

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0