## NSN 5305-01-586-1960

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-586-1960

3a Thread Direction: Right-hand Thread Length: 0.316 inches Fastener Length: Between 2.239 inches and 2.269 inches Head Style: Flat chamfer Head Diameter: Between 0.365 inches and 0.375 inches Head Height: Between 0.133 inches and 0.150 inches Grip Diameter:
Right-hand Thread Length: 0.316 inches Fastener Length: Between 2.239 inches and 2.269 inches Head Style: Flat chamfer Head Diameter: Between 0.365 inches and 0.375 inches Head Height: Between 0.133 inches and 0.150 inches
Thread Length: 0.316 inches Fastener Length: Between 2.239 inches and 2.269 inches Head Style: Flat chamfer Head Diameter: Between 0.365 inches and 0.375 inches Head Height: Between 0.133 inches and 0.150 inches
0.316 inches Fastener Length: Between 2.239 inches and 2.269 inches Head Style: Flat chamfer Head Diameter: Between 0.365 inches and 0.375 inches Head Height: Between 0.133 inches and 0.150 inches
Fastener Length:Between 2.239 inches and 2.269 inchesHead Style:Flat chamferHead Diameter:Between 0.365 inches and 0.375 inchesHead Height:Between 0.133 inches and 0.150 inches
Between 2.239 inches and 2.269 inches <b>Head Style:</b> Flat chamfer <b>Head Diameter:</b> Between 0.365 inches and 0.375 inches <b>Head Height:</b> Between 0.133 inches and 0.150 inches
Head Style: Flat chamfer Head Diameter: Between 0.365 inches and 0.375 inches Head Height: Between 0.133 inches and 0.150 inches
Flat chamfer Head Diameter: Between 0.365 inches and 0.375 inches Head Height: Between 0.133 inches and 0.150 inches
Head Diameter: Between 0.365 inches and 0.375 inches Head Height: Between 0.133 inches and 0.150 inches
Between 0.365 inches and 0.375 inches Head Height: Between 0.133 inches and 0.150 inches
Head Height: Between 0.133 inches and 0.150 inches
Between 0.133 inches and 0.150 inches
Grin Diameter:
Between 0.2481 inches and 0.2487 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
Between 1.928 inches and 1.948 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1124 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5305-01-586-1960

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

