NSN 5305-01-586-9572

Machine Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-586-9572

2a2aThread Direction:Right-handThread Length:0.875 inchesFastener Length:0.875 inchesHead Style:PanHead Diameter:Between 0.357 inches and 0.373 inchesHead Height:Between 0.122 inches and 0.133 inchesInternal Drive Style:Cross recess type 1End Application:Mrap-rg33 socomThread Diameter:0.190 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):1050 pounds per square inchScrew Material:ZincHead Surface Treatment:ZincScrew Surface Treatment:ZincStank Surface Treatment:ZincStank Surface Treatment:ZincStank Surface Treatment:ZincShank Surface Treatment:ZincStank Surface Treatment:ZincShank Surf	Thread Class:
Right-hand Thread Length: 0.875 inches Fastener Length: 0.875 inches Head Style: Pan Head Diameter: Between 0.357 inches and 0.373 inches Head Height: Between 0.122 inches and 0.133 inches Internal Drive Style: Cross recess type 1 End Application: Mrap-rg33 socom Thread Diameter: 0.190 inches Thread Diameter: 0.190 inches Thread Diameter: 0.190 inches Thread Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 1050 pounds per square inchScrew Material:Steel Bearing Surface Of Head Surface Treatment: Zinc Strew Surface Treatment: ZincShank Surface Treatment:ZincShank Surface Treatment:ZincStand Surface Treatment:ZincShank Surface Treatment:ZincShank Surface Treatment:ZincStand Surface Treatment:ZincShank Surface Treatment:ZincStandStand	
Thread Length:0.875 inchesFastener Length:0.875 inchesHead Style:PanHead Diameter:Between 0.357 inches and 0.373 inchesHead Height:Between 0.122 inches and 0.133 inchesInternal Drive Style:Cross recess type 1End Application:Mrap-rg33 socomThread Diameter:0.190 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):1050 pounds per square inchScrew Material:SteelBearing Surface Of Head Surface Treatment:ZincLincStank Surface Treatment:ZincShank Surface Treatment:ZincStank S	Thread Direction:
Thread Length:0.875 inchesFastener Length:0.875 inchesHead Style:PanHead Diameter:Between 0.357 inches and 0.373 inchesHead Height:Between 0.122 inches and 0.133 inchesInternal Drive Style:Cross recess type 1End Application:Mrap-rg33 socomThread Diameter:0.190 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):1050 pounds per square inchScrew Material:SteelBearing Surface Of Head Surface Treatment:ZincLincStank Surface Treatment:ZincShank Surface Treatment:ZincStank S	Right-hand
0.875 inches Fastener Length: 0.875 inches Head Style: Pan Head Diameter: Between 0.357 inches and 0.373 inches Head Height: Between 0.122 inches and 0.133 inches Head Height: Cross recess type 1 End Application: Arap-rg33 socom Thread Diameter: 0.190 inches Thread y Per Inch (tpi): 24 Min. Tensile Strength (psi): 1050 pounds per square inch Screw Material: Steel Bearing Surface Of Head Surface Treatment: Zinc Head Surface Treatment: Zinc Shank Surface Treatment: Zinc	
0.875 inches Head Style: Pan Head Diameter: Between 0.357 inches and 0.373 inches Head Height: Between 0.122 inches and 0.133 inches Internal Drive Style: Cross recess type 1 End Application: Mrap-rg33 socom Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 1050 pounds per square inch Screw Material: Steel Bearing Surface Of Head Surface Treatment: Zinc Head Surface Treatment: Zinc Shank Surface Treatment: Zinc	
0.875 inches Head Style: Pan Head Diameter: Between 0.357 inches and 0.373 inches Head Height: Between 0.122 inches and 0.133 inches Internal Drive Style: Cross recess type 1 End Application: Mrap-rg33 socom Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 1050 pounds per square inch Screw Material: Steel Bearing Surface Of Head Surface Treatment: Zinc Head Surface Treatment: Zinc Shank Surface Treatment: Zinc	Fastener Length:
PanHead Diameter:Between 0.357 inches and 0.373 inchesHead Height:Between 0.122 inches and 0.133 inchesInternal Drive Style:Cross recess type 1End Application:Mrap-rg33 socomThread Diameter:0.190 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):1050 pounds per square inchScrew Material:SteelBearing Surface Of Head Surface Treatment:ZincZincStrenes Surface Treatment:ZincShank Surface Treatment:ZincShank Surface Treatment:ZincStand Surface Treatment:Stand Surface Treatment:Stand Surface Treatment:ZincStand Surface Treatment:Stand Surface Treatment:	-
PanHead Diameter:Between 0.357 inches and 0.373 inchesHead Height:Between 0.122 inches and 0.133 inchesInternal Drive Style:Cross recess type 1End Application:Mrap-rg33 socomThread Diameter:0.190 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):1050 pounds per square inchScrew Material:SteelBearing Surface Of Head Surface Treatment:ZincZincStrenes Surface Treatment:ZincShank Surface Treatment:ZincShank Surface Treatment:ZincStand Surface Treatment:Stand Surface Treatment:Stand Surface Treatment:ZincStand Surface Treatment:Stand Surface Treatment:	Head Style:
Between 0.357 inches and 0.373 inchesHead Height:Between 0.122 inches and 0.133 inchesInternal Drive Style:Cross recess type 1End Application:Mrap-rg33 socomThread Diameter:0.190 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):1050 pounds per square inchScrew Material:SteelBearing Surface Of Head Surface Treatment:ZincLincStrew Surface Treatment:ZincShank Surface Treatment:ZincStanta Surface Treatment:ZincStanta Surface Treatment:ZincStanta Surface Treatment:ZincStanta Surface Treat	-
Head Height:Between 0.122 inches and 0.133 inchesInternal Drive Style:Cross recess type 1End Application:Mrap-rg33 socomThread Diameter:0.190 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):1050 pounds per square inchScrew Material:SteelBearing Surface Of Head Surface Treatment:ZincLincScrew Surface Treatment:ZincShank Surface Treatment:ZincStant Surface Treatment:ZincStant Surface Treatment:ZincStant Surface Treatment:ZincStant Surface	Head Diameter:
Between 0.122 inches and 0.133 inches Internal Drive Style: Cross recess type 1 End Application: Mrap-rg33 socom Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 1050 pounds per square inch Screw Material: Steel Bearing Surface Of Head Surface Treatment: Zinc Head Surface Treatment: Zinc Screw Surface Treatment: Zinc Shank Surface Treatment: Zinc	Between 0.357 inches and 0.373 inches
Between 0.122 inches and 0.133 inches Internal Drive Style: Cross recess type 1 End Application: Mrap-rg33 socom Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 1050 pounds per square inch Screw Material: Steel Bearing Surface Of Head Surface Treatment: Zinc Head Surface Treatment: Zinc Screw Surface Treatment: Zinc Shank Surface Treatment: Zinc	Head Height:
Internal Drive Style:Cross recess type 1End Application:Mrap-rg33 socomThread Diameter:0.190 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):1050 pounds per square inchSteelBearing Surface Of Head Surface Treatment:ZincZincStreew Surface Treatment:ZincStrew Surface Treatment:ZincStrew Surface Treatment:ZincStrew Surface Treatment:ZincStrem Surface Treatment:ZincStank Surface Treatment:Stank Surface Treatment:Stank Surface Treatment:Stank Surface Treatment:Stank Surface Treatment: <td>-</td>	-
Cross recess type 1 End Application: Mrap-rg33 socom Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 1050 pounds per square inch Screw Material: Steel Bearing Surface Of Head Surface Treatment: Zinc Head Surface Treatment: Zinc Screw Surface Treatment: Zinc Shank Surface Treatment: Zinc	
End Application: Mrap-rg33 socom Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 1050 pounds per square inch Screw Material: Steel Bearing Surface Of Head Surface Treatment: Zinc Head Surface Treatment: Zinc Screw Surface Treatment: Zinc Shank Surface Treatment: Zinc Shank Surface Treatment: Zinc	-
Mrap-rg33 socom Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 1050 pounds per square inch Screw Material: Steel Bearing Surface Of Head Surface Treatment: Zinc Head Surface Treatment: Zinc Screw Surface Treatment: Zinc Shank Surface Treatment: Zinc Thread Series Designator:	
Thread Diameter:0.190 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):1050 pounds per square inchScrew Material:SteelBearing Surface Of Head Surface Treatment:ZincHead Surface Treatment:ZincScrew Surface Treatment:ZincShank Surface Treatment:ZincStanc	
Thready Qty Per Inch (tpi):24Min. Tensile Strength (psi):1050 pounds per square inchScrew Material:SteelBearing Surface Of Head Surface Treatment:ZincHead Surface Treatment:ZincScrew Surface Treatment:ZincShank Surface Treatment:ZincSta	
24 Min. Tensile Strength (psi): 1050 pounds per square inch Screw Material: Steel Bearing Surface Of Head Surface Treatment: Zinc Head Surface Treatment: Zinc Screw Surface Treatment: Zinc Shank Surface Treatment: Zinc Thread Series Designator:	0.190 inches
Min. Tensile Strength (psi): 1050 pounds per square inch Screw Material: Steel Bearing Surface Of Head Surface Treatment: Zinc Head Surface Treatment: Zinc Screw Surface Treatment: Zinc Shank Surface Treatment: Zinc Thread Series Designator:	Thready Qty Per Inch (tpi):
1050 pounds per square inch Screw Material: Steel Bearing Surface Of Head Surface Treatment: Zinc Head Surface Treatment: Zinc Screw Surface Treatment: Zinc Shank Surface Treatment: Zinc	24
Screw Material: Steel Bearing Surface Of Head Surface Treatment: Zinc Head Surface Treatment: Zinc Screw Surface Treatment: Zinc Shank Surface Treatment: Zinc Thread Series Designator:	Min. Tensile Strength (psi):
Steel Bearing Surface Of Head Surface Treatment: Zinc Head Surface Treatment: Zinc Screw Surface Treatment: Zinc Shank Surface Treatment: Zinc Thread Series Designator:	1050 pounds per square inch
Bearing Surface Of Head Surface Treatment: Zinc Head Surface Treatment: Zinc Screw Surface Treatment: Zinc Shank Surface Treatment: Zinc Thread Series Designator:	Screw Material:
Zinc Head Surface Treatment: Zinc Screw Surface Treatment: Zinc Shank Surface Treatment: Zinc Thread Series Designator:	Steel
Head Surface Treatment: Zinc Screw Surface Treatment: Zinc Shank Surface Treatment: Zinc Thread Series Designator:	Bearing Surface Of Head Surface Treatment:
Zinc Screw Surface Treatment: Zinc Shank Surface Treatment: Zinc Thread Series Designator:	Zinc
Screw Surface Treatment: Zinc Shank Surface Treatment: Zinc Thread Series Designator:	Head Surface Treatment:
Zinc Shank Surface Treatment: Zinc Thread Series Designator:	Zinc
Shank Surface Treatment: Zinc Thread Series Designator:	Screw Surface Treatment:
Zinc Thread Series Designator:	Zinc
Thread Series Designator:	Shank Surface Treatment:
-	Zinc
Unc	Thread Series Designator:
	Unc
Shelf Life:	Shelf Life:
N/a	N/a
Unit Of Measure:	Unit Of Measure:
Demilitarization:	Demilitarization:
No	No

NSN 5305-01-586-9572

Machine Screw - Page 2 of 2

Fiig: A500d0

