NSN 5305-01-587-1305

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-587-1305 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** 1.323 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches Single Shear Strength: 95000 pounds per square inch **Point Style:** Flat **Internal Drive Style:** Cross recess type iii **Thread Diameter:** 0.164 inches **Grip Length:** 1.000 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Steel comp 4140 or steel comp 4340 or steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-562 military specification single material response or ams 6415 assn standard single material response or mil-s-5000 military specification single material response or mil-s-6049 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:**

N/a

Unjf

Shelf Life:

NSN 5305-01-587-1305

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-562 spec.