# NSN 5305-01-587-2969

Close Tolerance Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-587-2969

Thread	Class:
IIIIcau	<b>UIA33</b> .

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

0.403 inches

## Fastener Length:

3.403 inches

#### Head Style:

Flat countersunk

#### Head Diameter:

0.507 inches

Grip Diameter:

Between 0.248 inches and 0.249 inches

#### Internal Drive Style:

## High-torque

Thread Diameter:

0.250 inches

## Grip Length:

3.000 inches

## Thready Qty Per Inch (tpi):

28

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### **Product Name:**

Bolt shear 100 degrees flush head offset cruciform offset cruciform ribbed and dovetail slot 95 ksi fsu

#### Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740

#### Surface Treatment:

Cadmium and chromate

#### **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A003b0