NSN 5305-01-588-7184

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-588-7184 **Thread Class:** 6g **Thread Direction:** Right-hand Thread Length: 50.0 millimeters **Fastener Length:** 50.0 millimeters **Head Style:** Hexagon extended washer **Head Height:** 11.2 millimeters Width Between Flats: 22.0 millimeters **Extended Washer Diameter:** 31.0 millimeters **Washer Quantity: Internal Drive Style:** W/o internal drive **End Application:** 2355-01-529-2246, mine resistant vehicle **Thread Diameter:** 16.0 millimeters Min. Tensile Strength (psi): 130 pounds per square inch **Hardness Rating:** 27.0 rockwell c **Thread Pitch In Millimeters:** 2.0 **Product Name:** Metric vibration-resistant flange-head medium strength steel Color: Black Material: Steel **Supplementary Features:** Material is similar to class 10.9 steel; all are stronger than both gr 5 and metric 8.8 steel screws **Thread Series Designator:** Μ Shelf Life:

N/a

NSN 5305-01-588-7184

Assembled Washer Screw - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0