Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-588-7395

| | hread Direction: |
|---|---|
| F | Right-hand |
| Т | hread Length: |
| 0 | .500 inches |
| F | astener Length: |
| 0 | .500 inches |
| H | lead Style: |
| ŀ | lexagon extended washer |
| F | lead Height: |
| 0 | .242 inches |
| E | Extended Washer Diameter: |
| 0 | .500 inches |
| E | xtended Washer Thickness: |
| 0 | .250 inches |
| ۷ | Vasher Quantity: |
| 1 | |
| h | nternal Drive Style: |
| ۷ | V/o internal drive |
| E | nd Application: |
| 5 | 895-01-561-3705, satellite communication subsystem |
| Т | hread Diameter: |
| 0 | .164 inches |
| Т | hready Qty Per Inch (tpi): |
| 1 | 8 |
| F | lardness Rating: |
| 3 | 4.0 rockwell c |
| Т | hread Pitch In Millimeters: |
| 1 | .3 |
| F | Primary Washer Outside Diameter: |
| 0 | .500 inches |
| F | Primary Washer Style: |
| F | lat |
| F | Product Name: |
| S | Sealing hex washer head selfing drilling (tapping) screw m8 |
| N | laterial: |
| S | Steel comp 410 |
| S | Surface Treatment: |
| Z | linc |
| S | Supplementary Features: |
| | apping drill point is no 2 |
| S | Shelf Life: |
| | I/a |

NSN 5305-01-588-7395

Assembled Washer Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0