NSN 5305-01-588-8519

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-588-8519 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.407 inches and 0.438 inches **Fastener Length:** Between 0.407 inches and 0.438 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type iii **End Application:** 2350-01-506-0132 armored reconnaissance-airborne assault **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 1050 pounds per square inch **Product Name:** Screw, machine, pan head, cross-recessed **Screw Material:** Steel **Head Surface Treatment:** Zinc **Screw Surface Treatment:** Zinc **Head Surface Treatment Specification:** Astm b633-78, fe/zn 5, type ii assn standard single treatment response **Screw Surface Treatment Specification:** Astm b633-78, fe/zn 5, type ii assn standard single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a **Unit Of Measure:**

NSN 5305-01-588-8519

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0