Socket Head Cap Screw - Page 1 of 2



0689

V	iew Online at https://aerobasegroup.com/nsn/5305-01-589-0
т	hread Direction:
R	ight-hand
Т	hread Length:
2	0.0 millimeters
F	astener Length:
2	0.0 millimeters
Н	lead Style:
P	an no. 2
Η	ead Diameter:
1	6.0 millimeters
Н	lead Height:
1	0.0 millimeters
r	nternal Drive Style:
	lexagon
E	nd Application:
2	350-01-555-3697 unmanned ground vehicle, tracked
Γ	hread Diameter:
	0.0 millimeters
٨	/idth Across Flats:
;	.0 millimeters
V	lin. Tensile Strength (psi):
	74000 pounds per square inch
4	ardness Rating:
	7.0 rockwell c
	hread Pitch In Millimeters:
I	.5
E	xternal Thread Tolerance Class:
5	g6g
P	roduct Name:
s	ocket cap screw
N	laterial:
s	teel
s	urface Treatment:
Z	inc
Т	hread Series Designator:
N	1
s	helf Life:
	/a
U	nit Of Measure:
	emilitarization:

NSN 5305-01-589-0689

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

