## NSN 5305-01-589-9586

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-589-9586 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.403 inches **Fastener Length:** Between 2.138 inches and 2.168 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.477 inches and 0.492 inches **Head Height:** Between 0.140 inches and 0.150 inches **Grip Diameter:** Between 0.249 inches and 0.250 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.740 inches and 1.760 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5790 pounds per square inch **Product Name:** Bolt, flat pan head Material: Steel comp 4140 or steel comp 4340 or steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification single material response or ams 6415 assn standard single material response or mil-s-5000 military specification single material response or mil-s-6049 military specification single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig: A003b0

No

## NSN 5305-01-589-9586

Close Tolerance Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.