## NSN 5305-01-590-5990

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-590-5990

Thread Direction:				
Right-hand				
Thread Length:				
7.5 millimeters				
Fastener Length:				
Between 17.2 millimeters and 17.8 millimeters				
Head Style:				
Pan no. 2				
Head Diameter:				
Between 7.7 millimeters and 8.0 millimeters				
Head Height:				
Between 2.2 millimeters and 2.4 millimeters				
Grip Diameter:				
Between 3.965 millimeters and 3.990 millimeters				
Internal Drive Style:				
Offset cruciform (torque set)				
Thread Diameter:				
4.0 millimeters				
Grip Length:				
Between 9.8 millimeters and 10.2 millimeters				
Min. Tensile Strength (psi):				
1100 megapascals				
Hardness Rating:				
36.0 rockwell c and 40.0 rockwell c				
Thread Pitch In Millimeters:				
0.7				
External Thread Tolerance Class:				
4h6h				
Product Name:				
Screw, close tolerance pan head offset cruciform recess alloy steel, 1100 mpa, metric				
Material:				
Steel comp e4340 or steel comp 8740				
Material Specification:				
Mil-s-5000 military specification single material response or mil-s-6049 military specification single material response				
Surface Treatment:				
Cadmium				
Surface Treatment Specification:				
Qq-p-416, type ii, class 2 federal specification single treatment response				
Thread Series Designator:				
Mj				
Shelf Life:				
N/a				

## NSN 5305-01-590-5990

Close Tolerance Screw - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.