NSN 5305-01-590-7444

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-590-7444

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.720 inches and 0.750 inches |
| Fastener Length: |
| Between 0.720 inches and 0.750 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.365 inches and 0.375 inches |
| Head Height: |
| Between 0.244 inches and 0.250 inches |
| Internal Drive Style: |
| Hexagon |
| End Application: |
| Stryker |
| Thread Diameter: |
| 0.250 inches |
| Width Across Flats: |
| Between 0.188 inches and 0.190 inches |
| Thready Qty Per Inch (tpi): |
| |
| Min. Tensile Strength (psi): |
| 2540 pounds per square inch |
| Product Name: |
| Screw, cap, socket head, hexagon Material: |
| |
| Steel comp 316 or steel comp 316 |
| Material Specification: |
| Astm f593 assn standard single material response Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-01-590-7444

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

