

View Online at <https://aerobasegroup.com/nsn/5305-01-591-1380>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.276 inches

Fastener Length:

1.838 inches

Head Style:

Flat fillister

Head Diameter:

Between 0.265 inches and 0.270 inches

Head Height:

Between 0.088 inches and 0.102 inches

Grip Diameter:

0.255 mils

Point Diameter:

Between 0.1625 inches and 0.1635 inches

Point Style:

Flat

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.164 inches

Grip Length:

1.562 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

2240 pounds per square inch

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification single material response or mil-s-5000 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.