NSN 5305-01-591-1380

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-591-1380 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** 1.838 inches **Head Style:** Flat fillister **Head Diameter:** Between 0.265 inches and 0.270 inches **Head Height:** Between 0.088 inches and 0.102 inches **Grip Diameter:** 0.255 mils **Point Diameter:** Between 0.1625 inches and 0.1635 inches **Point Style:** Flat **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.164 inches **Grip Length:** 1.562 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 2240 pounds per square inch Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification single material response or mil-s-5000 military specification single material response or mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response

N/a

Unjc

Shelf Life:

Thread Series Designator:

NSN 5305-01-591-1380

Close Tolerance Screw - Page 2 of 2



Unit Of Mea	sure:
-------------	-------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.