

View Online at <https://aerobasegroup.com/nsn/5305-01-591-2238>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.641 inches

**Fastener Length:**

Between 2.314 inches and 2.344 inches

**Head Style:**

Fillister countersunk

**Head Diameter:**

Between 0.510 inches and 0.564 inches

**Head Height:**

0.018 inches

**Grip Diameter:**

0.374 mils and 0.375 centimeters

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.375 inches

**Grip Length:**

1.678 mils and 1.698 centimeters

**Thready Qty Per Inch (tpi):**

24

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

Screw-close tolerance, 100 degrees countersunk, reduced head, hi-torque, non-magnetic cres (125 ksi fsu)

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams 2700 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0