NSN 5305-01-592-6251

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-592-6251 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** Between 1.008 inches and 1.018 inches **Head Style:** Flat countersunk undercut **Head Diameter:** 0.375 inches **Head Height:** 0.052 inches **Internal Drive Style:** Tri-wing recess **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 1300 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Captive screw **Special Features:** Stud material: 8740 alloy steel per ams 6322, heat treat to 160 ksi min. Ultimate tensile strength Color: Yellow Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 3 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-592-6251

Panel Screw Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0