NSN 5305-01-593-5950

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-593-5950

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.323 inches |
| Fastener Length: |
| 3.198 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.357 inches and 0.373 inches |
| Head Height: |
| Between 0.122 inches and 0.133 inches |
| Grip Diameter: |
| Between 0.188 inches and 0.189 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| 2.875 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Product Name: |
| Bolt, pan head, close tolerance, short thread, cruciform recess, alloy steel |
| Material: |
| Steel comp 4140 or steel comp 4340 or steel comp 8740 |
| Material Specification: |
| Mil-s-5626 assn standard single material response or ams 6415 assn standard single material response or mil-s-6049 assn standard single |
| material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, ty ii, class 2 assn standard single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5305-01-593-5950

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.