## NSN 5305-01-595-1479

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-595-1479 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.180 inches **Fastener Length:** 0.500 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.260 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** 0.375 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches **Hole Diameter:** 0.100 inches First Diameter From Head: 0.095 inches **Second Diameter From Head:** 0.138 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.138 inches **Hole Quantity: Hole Type:** Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c **Hole Configuration Style:** Double hexagon longitudinal hole **Externally Relieved Body Diameter Quantity:** 

\_ . . .

Product Name:

Screw, captive, stainless steel, paasivated

## NSN 5305-01-595-1479

Externally Relieved Body Screw - Page 2 of 2



Special Features:
Material is steel ams6322
Material:
Steel
Surface Treatment:
Passivate
Thread Series Designator
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0