## NSN 5305-01-595-4648

Drive Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-595-4648

| Fastener Length:   |
|--|
| Between 0.235 inches and 0.265 inches                      |
| Head Style:  |
| Button   |
| Head Diameter:   |
| Between 0.193 inches and 0.211 inches                      |
| Head Height:   |
| Between 0.075 inches and 0.086 inches                      |
| Pilot Diameter:  |
| Between 0.092 inches and 0.096 inches                      |
| Pilot Length:  |
| 0.047 inches   |
| Nonmachine Thread Style:                                   |
| Drive screw (type u)                                       |
| Nonmachine Thread Diameter:                                |
| 0.112 inches   |
| Special Features:  |
| Heat treated to: 35 to 45 hrc                              |
| Material:  |
| Stainless steel  |
| Material Specification:                                    |
| Ams 5504 (uns41000) assn standard single material response |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:                           |
| Astm a 380 assn standard single treatment response         |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A003b0   |
|  |
|  |