NSN 5305-01-597-0690

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-597-0690 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.395 inches **Fastener Length:** 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Internal Drive Style:** Cross recess type iii **End Application:** E-3 aircraft **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Product Name:** Screw, pan head, cross recess, full threaded, a286 cres, self-locking **Screw Material:** Stainless steel **Locking Feature Material:** Plastic polyamide **Screw Material Specification:** Ams5737 assn standard single material response **Locking Feature Material Specification:** Mil-dtl-18240, type p military specification single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, t2, c2 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-597-0690

Machine Screw - Page 2 of 2



| _ | | | | | | | | | | |
|----|---|---|---|---|---|-----|----|---|---|--|
| וו | 0 | m | ш | м | • | iza | 31 | ^ | n | |
| | | | | | | | | | | |

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-dtl-18240 spec.