## NSN 5305-01-597-5721

**Thread Class:** 

2a

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-597-5721

Thread Direction:
Right-hand
Fastener Length:
0.750 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.256 inches and 0.294 inches
Head Height:
Between 0.087 inches and 0.097 inches
Washer Quantity:
2
Internal Drive Style:
Cross recess type 1
End Application:
77c734280g001 an/blq-10a (v) 1 system with pepi 3000
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Secondary Washer Relationship To Primary Washer:
Not identical
Secondary Washer Style:
Flat
Primary Washer Outside Diameter:
0.250 inches
Secondary Washer Outside Diameter:
Between 0.302 inches and 0.322 inches
Primary Washer Style:
Split helical ring
Primary Washer Material Thickness:
0.031 inches
Secondary Washer Material Thickness:
Between 0.025 inches and 0.035 inches
Product Name:
Pan head captive panel screw phillips
Material:
Steel comp 302 and steel comp 303 and steel comp 304
Surface Treatment:
Passivate

## NSN 5305-01-597-5721

Assembled Washer Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0