
NSN 5305-01-598-8543

Socket Head Cap Screw - Page 1 of 2





12.9 Thread Direction: Right-hand Thread Length: Between 44.0 millimeters and 54.0 millimeters Fastener Length: 130.0 millimeters Head Style: Flat chamfer Head Diameter: 24.0 millimeters Head Height: 16.0 millimeters Width Between Flats:

Thread Class:

14.0 millimeters

Internal Drive Style:

Hexagon

End Application:

3895-01-577-2425 paving machine, bitumonous material

Thread Diameter:

16.0 millimeters

Width Across Flats:

14.0 millimeters

Nonstandard Thread Pitch Diameter:

-14.0/+18.0 millimeters

Min. Tensile Strength (psi):

174000 pounds per square inch

Hardness Rating:

39.0 rockwell c

Thread Pitch In Millimeters:

2.0

Product Name:

Screw, cap, socket

Special Features:

Class: 5g6g

Color:

Black

Material:

Steel

Material Specification:

Din 912 international std/spec all material responses and iso 4762 international std/spec all material responses

NSN 5305-01-598-8543

Socket Head Cap Screw - Page 2 of 2

Surface Treatment:

Oxide

Thread Series Designator:

Μ

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

