NSN 5305-01-598-9146

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-598-9146 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.626 inches **Fastener Length:** Between 2.049 inches and 2.079 inches **Head Style:** Flat countersunk **Head Diameter:** 1.214 inches **Head Height:** Between 0.231 inches and 0.241 inches **Grip Diameter:** Between 0.623 inches and 0.624 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.625 inches **Grip Length:** 1.428 mils and 1.448 centimeters Thready Qty Per Inch (tpi): 18 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, 100 degrees flat head, offset cruciform Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Material Specification:** II-s-5626 military specification 10th material response or mil-s-5000 military specification single material response or mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-598-9146

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.