## NSN 5305-01-598-9262

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-598-9262 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** 0.500 inches **Head Style:** Hexagon extended washer **Head Height:** Between 0.105 inches and 0.120 inches Width Between Flats: Between 0.305 inches and 0.312 inches **Extended Washer Diameter:** Between 0.384 inches and 0.414 inches **Extended Washer Thickness:** Between 0.019 inches and 0.031 inches **Washer Quantity: Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 **Primary Washer Outside Diameter:** 0.384 mils and 0.414 centimeters **Primary Washer Style:** Flat **Primary Washer Material Thickness:** Between 0.019 inches and 0.031 inches **Product Name:** Unslotted indented hex washr head thread cutting screw Material: Steel **Surface Treatment:** Zinc **Surface Treatment Specification:** Astm f1941, fe/zn 3at assn standard single treatment response **Thread Series Designator:** Unc

## NSN 5305-01-598-9262

Assembled Washer Screw - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0