NSN 5305-01-599-3175

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-599-3175 **Thread Class:** 6g **Thread Direction:** Right-hand Thread Length: Between 24.5 millimeters and 27.5 millimeters **Fastener Length:** Between 64.2 millimeters and 65.8 millimeters **Head Style:** Fillister **Head Diameter:** Between 14.8 millimeters and 15.3 millimeters **Head Height:** Between 1.4 millimeters and 1.9 millimeters **Shoulder Diameter:** 10.7 millimeters first shoulder and 10.9 millimeters first shoulder **Shoulder Length:** 5.2 millimeters first shoulder and 6.8 millimeters first shoulder **End Application:** 6115-01-561-7718 generator set, diesel engine **Thread Diameter:** 10.0 millimeters **Thread Pitch In Millimeters:** 1.5 **Shoulder Shape:** Ribbed first shoulder **Product Name:** Stud, knurled Color: Black Material: Steel property class 8.8 **Material Specification:** Sae j1199, class 8.8 assn standard single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924d, class 1 military specification single treatment response **Thread Series Designator:**

Μ

Shelf Life:

N/a

NSN 5305-01-599-3175

Shoulder Screw - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924d spec.