3a

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-601-7151



## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.533 inches and 0.593 inches Fastener Length: Between 1.063 inches and 1.073 inches **Head Style:** Fillister **Head Diameter:** 0.625 inches **Head Height:** Between 0.285 inches and 0.300 inches Locking Feature: Patch **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): Hardness Rating: 36.0 rockwell c and 42.0 rockwell c **Chamfer Angle:** 45.0 degrees **Product Name:** Bolt, self-locking **Special Features:** Heat treat to 160, 000 psi ultimate tensile strength Material: Steel comp 4340 **Material Specification:** Mil-s-5000 military specification single material response Surface Treatment: Cadmium **Surface Treatment Specification:**

Qq-p-416, type 2, class 3 assn standard single treatment response

## **Thread Series Designator:**

Unf

28

## NSN 5305-01-601-7151

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

## Mil-std (military Standard):

Mil-s-5000 spec.

