## NSN 5305-01-603-1094

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-603-1094

Thread Direction:		
Right-hand		
Thread Length:		
30.0 millimeters		
Fastener Length:		
31.20 millimeters		
Head Style:		
Flat countersunk		
Head Diameter:		
3.60 millimeters		
Internal Drive Style:		
Cross recess type ii		
End Application:		
5905-00-433-6483		
Thread Diameter:		
2.2 millimeters		
Min. Tensile Strength (psi):		
80000 pounds per square inch		
Thread Pitch In Millimeters:		
0.45		
Countersink Angle:		
Between 90.0 degrees and 92.0 degrees		
Product Name:		
Screw, machine-flat head, 90 degree cross-recessed (metric)		
Screw Material:		
Stainless steel		
Screw Material Specification:		
Fed-std-66 federal standard single material response		
Bearing Surface Of Head Surface Treatment:		
Passivate		
Head Surface Treatment:		
Passivate		
Screw Surface Treatment:		
Passivate		
Shank Surface Treatment:		
Passivate		
Bearing Surface Of Head Surface Treatment Specification:		
Qq-p-35 federal specification single treatment response		
Head Surface Treatment Specification:		
Qq-p-35 federal specification single treatment response		

**Screw Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

## NSN 5305-01-603-1094

Machine Screw - Page 2 of 2



<b>Shank Surface</b>	<b>Treatment S</b>	pecification:
----------------------	--------------------	---------------

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Μ

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A500d0