## NSN 5305-01-603-1094

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-603-1094

Thread Direction:
Right-hand
Thread Length:
30.0 millimeters
Fastener Length:
31.20 millimeters
Head Style:
Flat countersunk
Head Diameter:
3.60 millimeters
Internal Drive Style:
Cross recess type ii
End Application:
5905-00-433-6483
Thread Diameter:
2.2 millimeters
Min. Tensile Strength (psi):
80000 pounds per square inch
Thread Pitch In Millimeters:
0.45
Countersink Angle:
Between 90.0 degrees and 92.0 degrees
Product Name:
Screw, machine-flat head, 90 degree cross-recessed (metric)
Screw Material:
Stainless steel
Screw Material Specification:
Fed-std-66 federal standard single material response
Bearing Surface Of Head Surface Treatment:
Passivate
Head Surface Treatment:
Passivate
Screw Surface Treatment:
Passivate
Shank Surface Treatment:
Passivate
Bearing Surface Of Head Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Head Surface Treatment Specification:

**Screw Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

## NSN 5305-01-603-1094

Machine Screw - Page 2 of 2



<b>Shank Surface</b>	<b>Treatment S</b>	pecification:
----------------------	--------------------	---------------

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Μ

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A500d0