## NSN 5305-01-603-1353

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-603-1353

View Online at https://aerobasegroup.com/nsn/5305-01-603-1353
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.355 inches and 0.375 inches
Fastener Length:
Between 0.355 inches and 0.375 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.327 inches and 0.338 inches
Head Height:
Between 0.105 inches and 0.115 inches
Extended Washer Diameter:
Between 0.327 inches and 0.338 inches
Extended Washer Thickness:
Between 0.018 inches and 0.023 inches
Internal Drive Style:
Cross recess type 1
End Application:
A3266159-001
Thread Diameter:
0.164 inches
Features Provided:
Lock washer
Thready Qty Per Inch (tpi):
32
Product Name:
Screw, pan head, cross-recessed, single sems
Screw Material:
Stainless steel
Bearing Surface Of Head Surface Treatment:
Passivate
Head Surface Treatment:
Passivate
Screw Surface Treatment:
Passivate
Shank Surface Treatment:
Passivate
Bearing Surface Of Head Surface Treatment Specification:
Astm a380 assn standard single treatment response

## NSN 5305-01-603-1353

Machine Screw - Page 2 of 2



## **Head Surface Treatment Specification:**

Astm a380 assn standard single treatment response

**Screw Surface Treatment Specification:** 

Astm a380 assn standard single treatment response

**Shank Surface Treatment Specification:** 

Astm a380 assn standard single treatment response

**Special Features:** 

Lock washer has internal teeth

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A500d0