## NSN 5305-01-603-1353

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-603-1353



**Thread Class:** 2a **Thread Direction: Right-hand Thread Length:** Between 0.355 inches and 0.375 inches Fastener Length: Between 0.355 inches and 0.375 inches Head Style: Pan no. 2 **Head Diameter:** Between 0.327 inches and 0.338 inches **Head Height:** Between 0.105 inches and 0.115 inches **Extended Washer Diameter:** Between 0.327 inches and 0.338 inches **Extended Washer Thickness:** Between 0.018 inches and 0.023 inches Internal Drive Style: Cross recess type 1 **End Application:** A3266159-001 **Thread Diameter:** 0.164 inches **Features Provided:** Lock washer Thready Qty Per Inch (tpi): 32 **Product Name:** Screw, pan head, cross-recessed, single sems **Screw Material:** Stainless steel **Bearing Surface Of Head Surface Treatment:** Passivate Head Surface Treatment: Passivate **Screw Surface Treatment:** Passivate **Shank Surface Treatment:** Passivate Bearing Surface Of Head Surface Treatment Specification:

Astm a380 assn standard single treatment response

## NSN 5305-01-603-1353

Machine Screw - Page 2 of 2



Head Surface Treatment Specification: Astm a380 assn standard single treatment response Screw Surface Treatment Specification: Astm a380 assn standard single treatment response Shank Surface Treatment Specification: Astm a380 assn standard single treatment response **Special Features:** Lock washer has internal teeth **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A500d0