## NSN 5305-01-603-1430

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-603-1430

Thread Olever
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.844 inches and 0.875 inches
Fastener Length:
Between 0.844 inches and 0.875 inches
Head Style:
Pan
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Internal Drive Style:
Torque-set ribbed
End Application:
Army
Thread Diameter:
0.1900 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
1200 pounds per square inch
Product Name:
Screw, machine, pan head, cruciform recess, carbon steel
Screw Material:
Steel
Screw Material Specification:
Sae air4127 national specification single material response
Screw Surface Treatment:
Zinc
Screw Surface Treatment Specification:
Astm b633, fe/zn 5, type ii assn standard single treatment response
Thread Series Designator:
Unf
Specification Data:
80205-nas-35207 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-603-1430

Machine Screw - Page 2 of 2



em			

No

Fiig:

A500d0