NSN 5305-01-603-1439

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-603-1439

view Offiline at https://defobasegroup.com/nsi//3303-01-003-14-03
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.844 inches and 0.875 inches
Fastener Length:
Between 0.844 inches and 0.875 inches
Head Style:
Pan
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Internal Drive Style:
Cross recess type ii
End Application:
B-2 bomber
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
60000 pounds per square inch
Product Name:
Screw, machine-pan head, cross-recessed, carbon steel, zinc plated, unf-2a
Screw Material:
Steel
Screw Material Specification:
Fed standard no 66 federal standard single material response
Bearing Surface Of Head Surface Treatment:
Zinc
Head Surface Treatment:
Zinc
Screw Surface Treatment:
Zinc
Shank Surface Treatment:
Zinc
Bearing Surface Of Head Surface Treatment Specification:
Astm b633-78, type 2 assn standard single treatment response
Head Surface Treatment Specification:

ricad ouridoc ricalinent opcomoditon.

Astm b633-78, type 2 assn standard single treatment response

NSN 5305-01-603-1439

Machine Screw - Page 2 of 2



Screw Surface Treatment Specification:

Astm b633-78, type 2 assn standard single treatment response

Shank Surface Treatment Specification:

Astm b633-78, type 2 assn standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0