## NSN 5305-01-603-1439

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-603-1439



## **Thread Class:** 2a **Thread Direction: Right-hand Thread Length:** Between 0.844 inches and 0.875 inches Fastener Length: Between 0.844 inches and 0.875 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type ii **End Application:** B-2 bomber **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch **Product Name:** Screw, machine-pan head, cross-recessed, carbon steel, zinc plated, unf-2a Screw Material: Steel **Screw Material Specification:** Fed standard no 66 federal standard single material response **Bearing Surface Of Head Surface Treatment:** Zinc **Head Surface Treatment:** Zinc **Screw Surface Treatment:** Zinc **Shank Surface Treatment:** Zinc Bearing Surface Of Head Surface Treatment Specification: Astm b633-78, type 2 assn standard single treatment response Head Surface Treatment Specification:

Astm b633-78, type 2 assn standard single treatment response

## NSN 5305-01-603-1439

Machine Screw - Page 2 of 2



Screw Surface Treatment Specification: Astm b633-78, type 2 assn standard single treatment response Shank Surface Treatment Specification: Astm b633-78, type 2 assn standard single treatment response Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A500d0